

# TEUPEN<sup>®</sup>

...access redefined

## LEO23GT

Working height:  
23.00 m

Lateral reach:  
11.20 m

Machine width:  
0.98 m

Machine height:  
1.97 m

Weight:  
2,990 kg

- Compact design, travels through a one metre wide single door
- Light, low surface load for use on sensitive flooring
- Smooth, proportional electro-hydraulic controls
- Reliable and comprehensive safety control system
- Articulated design with two independently operable telescopic booms
- Automatic, multi-position & self leveling outriggers
- Height- and width adjustable tracks
- Dual Power (Diesel and A/C electric) for indoor and outdoor use

[www.TEUPEN.com](http://www.teupen.com)

Teupen Maschinenbau GmbH  
phone +49 2562 8161 0  
fax +49 2562 8161 888  
mail@teupen.com



### Compact tracked boom lift - LEO23GT

Accessing jobsites at height safely and efficiently often poses unsolvable challenges to building managers. Narrow entrances, confined work areas and floor load restrictions can make the use of standard aerial lifts impossible.

With the LEO Series<sup>®</sup>, Teupen offers the original tracked aerial lift in a complete range for demanding indoor and rugged outdoor applications from 13 to outstanding 50 metres working height.



**LEO**SERIES



# LEO23GT



The light LEO23GT can be towed on standard trailers. It can either be driven on the trailer or simply use its outrigger system.



With its compact dimensions the LEO23GT fits through most entrance doors. The sensitive electro-proportional controls allow precise maneuvering.

## Top features:

- Compact** – Fits through a one metre wide single door
- Light** – Low ground pressure to protect sensitive surfaces
- Versatile** – Highest maneuverability on white rubber tracks
- Easy** – Automatic self-levelling stabilisers
- Simple** – Color coded & well-arranged control panel
- Power** – Multiple power sources for indoor and outdoor work

## Overview: LEO Series models from 23 to 36 metres working height

Model	LEO23GT	LEO25T	LEO25Tplus	LEO30T	LEO36T
<b>Working height</b>	23,00 m	25,00 m	25,20 m	30,00 m	35,50 m
<b>Outreach</b>	11,20 m	12,50 m	15,00 m	14,00 m	13,90 m
<b>Weight</b>	2990 kg	2980 kg	3760 kg	4225 kg	4850 kg
<b>Width</b>	0,98 m	1,78 m	1,58 m	1,58 m	1,58 m
<b>Movable Jib</b>	-	-	-	✓	✓
<b>Adjustable tracks</b>	✓	✓	✓	✓	✓
<b>Rotatable basket</b>	✓	✓	✓	✓	✓

LEO = Model, Number = Metric Working height, G = Articulated, T = Telescopic



The automatic outrigger system levels out height differences perfectly. Additionally, three different outrigger setup positions are available.



A clearly arranged control panel with color coded functions and only four joysticks for the entire lift operation supports intuitive and safe handling even for inexperienced users.